

## 10 POUND CAPACITY PORTABLES

They're lightweight, rugged and completely portable...easy to load, easy to carry...ready to provide low cost control of welding quality in the shop or in the field. Reduce operating costs by providing your welding operators with fast access to electrodes at the point-of-work. There's a model exactly suited to your requirements.



### Thermometer/ Rod Lifter Accessory

Model T10 - for use with portable oven models 10 A-20 and 10B-20... a two compartment rod lifter with thermometer top mounted and protected.

### Model 10 A-20

Operates from any 115 volt, AC/DC source. Is equipped with rod lifter, pilot light and has 1" high false bottom to prevent moisture damage to electric connections. Oven temperature, not controlled by thermostat, averages 275° F. Provides absolute electrode stability when used in conjunction with temperature-controlled ovens.

### Model 10 N-20 Nuclear

Operates on 115 volt, AC only. Has two pilot lights and two thermostats that maintain oven temperature in 100° to 400° F range. Equipped with divided rod lifter with provision for thermometer - part 1029.

### Model 10 B-20

Operates on 115 volt, AC only. Has rod lifter, pilot light, and thermostat that maintains oven temperature in 100° F to 400° F range, providing independent control of electrode welding quality.

# ELECTRODE STABILIZING OVENS

## SPECIFICATIONS

	PORTABLE OVENS				COMPACT IN-SHOP MODELS			
	10 A-20	10 B-20	10 N-20	50	125	350	350A	1000
Capacity	10 to 20 lbs			50 to 70 lbs.	125 to 175 lbs.	350 to 400 lbs.		Sixteen 12" Spools/1000 lbs.
Outside Dimensions	7" dia. x 23" high			11" dia. x 23" high	16"h x 16" w x 24 1/2"d	22"h x 22"w x 24 1/2" d		39 3/4"h x 30 1/4"w x 30 3/4"d
Inside Dimensions	3" dia. x 19" high			7" dia. x 19" high	8 1/4"h x 9 3/4"w x 19"d	14"h x 16"w x 19"d		24"h x 21 3/4"w x 24"d
Unit Weight (approx.)	14 lbs.			32 lbs.	58 lbs	105 lbs.		330 lbs.
Electrode Size	up to 18"			up to 18"	up to 18"	up to 18"		up to 24"
Line Cord	3 wire - 8 ft.			3 wire- 8 ft.	3 wire - 8 ft.	3 wire - 8 ft.	None	None
Element	100W - 115 Volt	125W - 115 Volt	300W - 115 Volt	300 W - 115 Volt	1000 W - 115 V	1500 W - 115 V	1500 W-220/440 V	3000 W - 220/440 V- 1 Phase
Thermostat	No	Yes	Yes (2)	Yes	Yes	Yes		Yes
Pilot Light	Yes			Yes	Yes	Yes		Yes
Temp. Range	Av. 275° F	100° - 400° F		100° - 400° F	100° - 550° F	100° - 550° F		100° - 550° F
Door Latch	Lift Lid			Lift Lid	Push/Pull	Push/Pull		Push/Pull
Stacking	No			No	Yes	Yes		Yes

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Note: Weight capacity depends on electrode length.