

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MA370099G

Date Tested: 4/21/2016

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.796	383	6.021	883	9.242	1382
TC2	2.793	383	6.020	883	9.248	1382
TC3	2.793	383	6.011	883	9.244	1383
TC4	2.797	383	6.015	883	9.249	1383
TC5	2.793	383	6.016	882	9.244	1382
TC6	2.794	383	6.016	883	9.243	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015

Calibration Date: 10/26/2015

Precision Digital Voltage Meter SN: 2036021

Calibration Date: 10/26/2015

Machine re-calibration due date: 4/21/2017

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.

Technician: Scott T.

Date: 4/21/2016

Signature