

Miller ProHeat 35

Unit Serial Number: MC090110G Date Tested: 11/1/2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.791	382	6.012	882	9.233	1381
TC2	2.793	383	6.018	882	9.244	1382
TC3	2.794	383	6.010	882	9.238	1382
TC4	2.795	383	6.014	882	9.236	1382
TC5	2.785	383	6.010	882	9.241	1382
TC6	2.795	383	6.017	882	9.237	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015 Calibration Date: 12/17/2012

Precision Digital Voltage Meter SN: 2036021 Calibration Date: 12/17/2012

Machine re-calibration due date: 11/1/2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Sal H. Date: 11/1/2013

Signature