

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MC430032G

Date Tested: 03/04/2014

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.783	383	6.015	883	9.245	1383
TC2	2.798	384	6.026	883	9.249	1383
TC3	2.802	384	6.022	884	9.248	1383
TC4	2.804	384	6.024	884	9.249	1384
TC5	2.802	384	6.023	884	9.249	1384
TC6	2.806	384	6.033	884	9.250	1384
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: 08/09/2013

Precision Digital Voltage Meter SN: 2142011

Calibration Date: 08/09/2013

Machine re-calibration due date: 03/04/2015

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:

Guo Rodin

Date:

03/04/14

Signature