

### Miller ProHeat 35

Unit Serial Number: MD040127G

Date Tested: 8/27/2015

### Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.794	383	6.020	883	9.242	1383
TC2	2.790	383	6.014	883	9.245	1383
TC3	2.793	383	6.018	883	9.246	1383
TC4	2.791	383	6.017	883	9.245	1383
TC5	2.792	383	6.017	883	9.247	1383
TC6	2.793	383	6.014	883	9.245	1383
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

#### Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2969020 Calibration Date: 11/21/2014

Precision Digital Voltage Meter SN: 3030025 Calibration Date: 1/23/2015

Machine re-calibration due date: 8/27/2016

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: K.DEVANE

Date: 8/27/2015

Signature