

### Miller ProHeat 35

Unit Serial Number: MD170246G

Date Tested: 2/25/2016

### Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.789	382	6.015	882	9.243	1381
TC2	2.793	382	6.019	882	9.242	1381
TC3	2.785	382	6.017	882	9.242	1381
TC4	2.789	382	6.012	882	9.239	1382
TC5	2.783	382	6.008	882	9.241	1382
TC6	2.788	382	6.012	881	9.241	1381
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

#### Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1897018 Calibration Date: 9/04/2015

Precision Digital Voltage Meter SN: US36049893 Calibration Date: 09/04/2015

Machine re-calibration due date: 02/25/2017

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: K. DEVANE Date: 2/25/2016

Signature