



Calibration Certificate

Miller ProHeat 35

Unit Serial Number: ME040111G

Date Tested: 14-JUN-17

Certified Calibration

	Primary Standard					
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.782	381	6.012	881	9.236	1381
TC2	2.782	381	6.012	881	9.238	1381
TC3	2.788	382	6.019	882	9.244	1382
TC4	2.788	382	6.021	882	9.247	1382
TC5	2.785	382	6.010	882	9.244	1382
TC6	2.785	382	6.007	882	9.241	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2097001

Calibration Date: 13-MAR-17

Precision Digital Voltage Meter SN: 2142012

Calibration Date: 13-MAR-17


Machine re-calibration due date: 14-JUN-18

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:



Date: 14JUN17

Signature